

# LOGAMOL ETP

## High Performance Cutting Oil

LOGAMOL ETP is a light color high viscosity heavy duty tapping and cutting oil that suitable for ferrous metals, stainless steel, alloy steel as well as yellow metals. It contains special additives to prevent the formation of oil mist.

LOGAMOL ETP contains extreme pressure additives ensuring excellent cutting performance and increased life of the cutting tools. It ensures high quality surface finishing.

### Advice for Usage

- Avoid exposure to high bulk oil temperatures.
- In order to achieve maximum performance, fine finishes and optimum tool life in a circulating cutting process, the cutting oil, as far as possible, must kept free from solid particles, especially metal chips. Use a chip strainer to remove metal chips and large particles as much as possible. The cutting oil free from large metallic particles and chips should then be directed through a magnetic roller/blade to further remove fine metal particles before cutting oil returns to the main oil reservoir.

### Packaging

18 liters pail & 209 liters drum.

### Typical Properties

Characteristics	Test Method	Value
Color	Visual	Clear, Light Yellow
Specific Gravity @ 20°C, g/cm <sup>3</sup>	D792	1.13
Viscosity @ 40°C, cSt	D445	50
Flash Point	D92	170 °C

### Customer Advice

For further assistance on product MSDS, recommendation or technical queries, please liaise with the regional technical services engineer or contact HQ technical engineers.